# 119/150 Loudspeakers

Energetic. Fun. Refined.

## INTERNAL USE ONLY

119 is a modern and high-performance, 2-way passive bookshelf loudspeaker. 150 is its larger, 3-way floor-standing sibling. Both allnew speaker models are energetic, conspicuously refined – and loads of fun.

Linn has a long history of designing and manufacturing compact loudspeakers with excellent performance that belies their size. 119 and 150 reflect this pedigree, with a new performance benchmark and the addition of peerless versatility when it comes to system-building.

With 119 and 150, the goal was to create fundamentally entertaining loudspeakers, but with refinement, sophistication and neutrality, so that they would play any source material equally well and equally enjoyably.

In response to feedback, another key focus was to make it easier than ever to upgrade systems to Exakt, using Linn speakers fed from a Selekt DSM.

119 and 150 are fitted with premium drive units, delivering excellent linear performance and excursion capability. Drawing from what we learned in the development of our flagship 360 loudspeakers, drive units are mounted at the very front of the baffle, with no grille, to minimise occlusion and improve excursion.

Component quality is high throughout. Lower-order crossovers in 119

and 150 are designed for signal purity and, as a result, lend the speakers speed and dynamism.

## Key points

- · Excellent linear performance and excursion
- · Electro-formed Linn logo tweeter guard
- · Lower-order crossovers for signal purity

## 119

- Rear-ported design delivers high-performance bass
- Bass augmentation filter further improves bass performance when fed from a Linn DSM
- · Optional black or silver pedestal stand

## 150

- Down-firing ports produce impactful and omnidirectional bass performance
- Optional aluminium upgrade plinth improves overall performance (available 2025)



	119	150
Channels	2	3
Room Correction	Space Optimisation with a Linn DSM	
Available Upgrades	Externally amplified Exakt with Selekt DSM or Exaktbox	Externally amplified Exakt with Selekt DSM or Exaktbox; 150 Upgrade Stand
Drive Units - Bass Driver	16cm with Nextel-coated paper diaphragm; large ferrite magnet motor system with high linear excursion	19cm and 16cm with Nextel-coated paper diaphragm; large ferrite magnet motor system with high linear excursion
Drive Units - Tweeter	19.55mm soft Sonomex dome; large ferrite magnet; voice coil in ferrofluid	
Frequency Response (+/- 6dB)	50Hz-20kHz	38Hz-20kHz
Binding Posts	x2 pairs	x3 pairs
Sensitivity	86dB	
Nominal Impedance	4Ω	
Finishes	Walnut, Oak, Black, White	
Dimensions	191mm (W) x 328mm (H) x 241mm (D)	210mm (W) x 936mm (H) x 297mm (D)
Weight	7.15 kg each	21.56 kg each