

PATHOS

THE UNORTHODOX APPROACH



AMPLID

PATHOS

AmpliD is the first of a new line of digital amplifiers from Pathos.

Completely balanced in Class D, it features a 70 Watt output power on each channel at 8 Ohm, and 130 Watt on each channel at 4 Ohm; it has 2 kinds of inputs (1 as stereo balanced XLR and 1 as stereo unbalanced RCA line).

Despite small dimensions, AmpliD provides great power and high sound quality. It reached state-of-the-art among all those digital amplifiers, that cannot be underestimated in terms of technological innovation.



AMPLI D



Aluminum has been used both for painting and for chassis, while on the upper part can be found our carved logo.

High quality components and superior technology allow this product to stand any comparison with the products of its category.

AmpliD is available in two finishes and, if combined with Converto EVO and In The Groove, will set up a perfect audio system both for digital and phono source.

This product is entirely handmade in Italy.

PATHOS

Pathos Acoustics
Via Palù n. 50/52
36040 Grumolo delle Abbadesse
Italy
www.pathosacoustics.com

The manufacturer reserves the right to introduce technical and external modifications without prior notice. Pathos® is a registered trademark. Copyright Pathos Acoustics. All Rights reserved.

THE UNORTHODOX APPROACH



Technical specifications:

STEREO POWER AMPLIFIER IN CLASS D, FULLY BALANCED

Output Power:	70W @ 8 Ohm 130W @ 4 Ohm
Frequency response:	1 Hz – 100 KHz
THD:	< 0,04%
Dumping factor:	50
S/N Ratio:	98dB
Input impedance:	47 KOhm
Analog inputs:	1 stereo balanced XLR 1 stereo unbalanced RCA line
Input sensitivity:	0,8 VRMS Unbalanced 0,8+0,8 VRMS Balanced
Output impedance:	0,16 Ohm
Gain:	29 dB Unbalanced 23 dB Balanced
Power consumption:	Min 8W Max 300W <0,5W standby mode
Dimensions:	230mm (D) x 200mm (W) x 70mm (H)
Net Weight:	5Kg