

Specifications

Model	Platinum 100 3G	Platinum 200 3G	Platinum 300 3G	Platinum C250 3G
System Format	2-way	3-way	3-way	3-way
Frequency response (-6dB) Free-Field	37 Hz - >60 kHz	32 Hz - >60 kHz	25 Hz - >60 kHz	48 Hz - >60 kHz
Frequency response (-6dB) In room	28 Hz - >60 kHz	23 Hz - >60 kHz	17 Hz - >60 kHz	30 Hz - >60 kHz
Sensitivity (2.83v @ 1m)	85 dB	88 dB	88 dB	88 dB
Nominal impedance	4 Ohms	4 Ohms	4 Ohms	4 Ohms
Minimum Impedance	4.0 Ohms @ 180 Hz	4.0 Ohms @ 2.5 kHz	4.0 Ohms @ 3.75 kHz	4.0 Ohms @ 150 Hz
Continuous Power Handling (RMS into 4 Ohms, Pink Noise with 6dB Crest Factor)	150 W	300 W	400 W	300 W
Recommended Amplifier Power(RMS into 4 Ohm, Music Signal)	75-300 W	150-600 W	200-800 W	150-600 W
Bass Alignment	HiVe II port system	HiVe II port system	Dual HiVe II port system	Sealed
Crossover Frequency	LF/HF: 2.85 kHz	LF/MF: 825 HzMF/HF: 3 kHz	LF/MF: 650 HzMF/HF: 3 kHz	LF/MF: 850 HzMF/HF: 3.5 kHz
Port Tuning Frequency	44 Hz	38 Hz	32 Hz	N/A
Drive Unit Complement	1 x 6" RDT III bass driver, 1 x MPD III tweeter	2 x 6" RDT III bass driver, 1 x 4" RDT III mid-range driver, 1 x MPD III tweeter	2 x 8" RDT III bass driver, 1 x 4" RDT III mid-range driver, 1 x MPD III tweeter	2 x 6" RDT III bass driver, 1 x 2.5" RDT III mid-range driver, 1 x MPD III tweeter
External Dimensions including Grille and Terminals (H x W x D)	398 x 225 x 325 mm 15.6 x 8.8 x 12.7"	1023.2 (1031.4)* x 368 x 454 mm 40.2 (40.6)* x 14.4 x 17.8"	1112.7 (1120.9)* x 430 x 525 mm 43.8 (44.1)* x 16.9 x 20.6"	225 x 630 x 326 mm 8.8 x 24.8 x 12.8"
External Dimensions including Outtrigger Feet and Spikes (H x W x D)	N/A	1039.7 (1047.9)* x 368 x 454 mm 40.9 (41.2)* x 14.4 x 17.8"	1129.2 (1137.4)* x 430 x 525 mm 44.4 (44.7)* x 16.9 x 20.6"	N/A
Weight (Each)	15.2 kg 33 lb 8 oz	35.8 kg 78 lb 14 oz	53.6 kg 118 lb 2 oz	25.4 kg 55 lb 15 oz
Finishes	Piano Ebony, Piano Black, Matte White			