

elipson® | CHROMA TURNTABLE



CHROMA 200

● Matt black



CHROMA 200 RIAA

● Matt black



CHROMA 200 RIAA BT

● Matt black



CHROMA 400

● Black
○ White
● Red



CHROMA 400 RIAA

● Black
○ White
● Red



CHROMA 400 RIAA BT

● Noir
○ White
● Red



CHROMA CARBON

● Carbon



CHROMA CARBON RIAA BT

● Carbon

elipson® | CHROMA TURNTABLE

	Chroma 200	Chroma 200 RIAA	Chroma 200 RIAA BT	Chroma 400
Chassis	PVC	PVC	PVC	Lacquered PMMA
Plate	Pressed steel	Pressed steel	Pressed steel	Pressed steel
Tonearm	Aluminium	Aluminium	Aluminium	Carbon
Cartridge	Ortofon OM10	Ortofon OM10	Ortofon OM10	Ortofon OM10
45 RPM Adaptor	Polyamid	Polyamid	Polyamid	Aluminium
Built-in electronics		High-end RIAA preamp	High-end RIAA preamp aptX Bluetooth Opto isolated USB output	
Colours	Matt black	Matt black	Matt black	Black, white, red
Dimensions (mm)	W450 x H120 x D380	W450 x H120 x D380	W450 x H120 x D380	W450 x H120 x D380
Weight	5 kg	5 kg	5 kg	5,8 kg

	Chroma 400 RIAA	Chroma 400 RIAA BT	Chroma carbon	Chroma Carbon RIAA BT
Chassis	Lacquered PMMA	Lacquered PMMA	PMMA	PMMA
Plate	Pressed steel	Pressed steel	Pressed steel	Pressed steel
Tonearm	Carbon	Carbon	Carbon	Carbon
Cartridge	Ortofon OM10	Ortofon OM10	Ortofon 2M RED	Ortofon 2M RED
45 RPM Adaptor	Aluminium	Aluminium	Aluminium	Aluminium
Built-in electronics	High-end RIAA preamp	High-end RIAA preamp aptX Bluetooth Opto isolated USB output		High-end RIAA preamp aptX Bluetooth Opto isolated USB output
Colours	Black, white, red	Black, white, red	Carbon covering	Carbon covering
Dimensions (mm)	W450 x H120 x D380	W450 x H120 x D380	W450 x H120 x D380	W450 x H120 x D380
Weight	5,8 kg	5,8 kg	5,8 kg	5,8 kg

RIAA module	MM	MC
Frequency response	25 Hz-20 kHz (-3 dB/+1 dB)	
Gain	40,5 dB	61 dB
Crosstalk	88 dB	78 dB
THD	0,006 %	0,05 %
Signal/noise ratio	82 dB	76 dB

BLUETOOTH module	
Bluetooth Class 2	2,5 mW - 4 dBm range : 10 m
Bluetooth 2.4 G	2.402 to 2.480 GHz

